

§ 1915.96

cleared from the danger area according to minimum safe distances established for and based on the type, model, and power of the equipment.

[47 FR 16986, Apr. 20, 1982, as amended at 49 FR 18295, Apr. 30, 1984; 54 FR 24334, June 7, 1989]

§ 1915.96 Work in or on lifeboats.

The provisions of this section shall apply to ship repairing, shipbuilding, and shipbreaking except that paragraph (b) of this section applies to ship repairing and shipbuilding only.

(a) Before employees are permitted to work in or on a lifeboat, either stowed or in a suspended position, the employer shall ensure that the boat is secured independently of the releasing gear to prevent the boat from falling due to accidental tripping of the releasing gear and movement of the davits or capsizing of a boat in chocks.

(b) Employees shall not be permitted to remain in boats while the boats are being hoisted into final stowed position.

(c) Employees shall not be permitted to work on the outboard side of lifeboats stowed on their chocks unless the boats are secured by gripes or otherwise secured to prevent them from swinging outboard.

§ 1915.97 Health and sanitation.

The provisions of this section shall apply to ship repairing, shipbuilding and shipbreaking, except where indicated otherwise.

(a) The employer shall provide all necessary controls, and the employees shall be protected by suitable personal protective equipment against the hazards identified under § 1915.99 of this part and those hazards for which specific precautions are required in subparts B, C, and D of this part.

(b) The employer shall provide adequate washing facilities for employees engaged in the application of paints or coatings or in other operations where contaminants can, by ingestion or absorption, be detrimental to the health of the employees. The employer shall encourage good personal hygiene practices by informing the employees of the need for removing surface contaminants by thorough washing or hands and face prior to eating or smoking.

29 CFR Ch. XVII (7-1-99 Edition)

(c) The employer shall not permit employees to eat or smoke in areas undergoing surface preparation or preservation or where shipbreaking operations produce atmospheric contaminants.

(d) The employer shall not permit employees engaged in ship repair work on a vessel to work in the immediate vicinity of uncovered garbage and shall ensure that employees working beneath or on the outboard side of a vessel are not subject to contamination by drainage or waste from overboard discharges.

(e) No minor under 18 years of age shall be employed in shipbreaking or related employments.

[52 FR 31886, Aug. 24, 1987]

§ 1915.98 First aid.

The provisions of this section shall apply to ship repairing, shipbuilding and shipbreaking.

(a) Unless a first aid room and a qualified attendant are close at hand and prepared to render first aid to employees on behalf of the employer, the employer shall furnish a first aid kit for each vessel on which work is being performed, except that when work is being performed on more than one small vessel at one pier, only one kit shall be required. The kit, when required, shall be kept close to the vessel and at least one employee, close at hand, shall be qualified to administer first aid to the injured.

(b) The first aid kit shall consist of a weatherproof container with individual sealed packages for each type of item. The contents of such kit shall contain a sufficient quantity of at least the following types of items:

Gauze roller bandages, 1 inch and 2 inch.
Gauze compress bandages, 4 inch.
Adhesive bandages, 1 inch.
Triangular bandage, 40 inch.
Ammonia inhalants and ampules.
Antiseptic applicators or swabs.
Burn dressing.
Eye dressing.
Wire or thin board splints.
Forceps and tourniquet.

(c) The contents of the first aid kit shall be checked before being sent out on each job and at least weekly on each job to ensure that the expended items are replaced.